

# Dictionaries; More on File Input / Output

Pedro Barahona  
DI/FCT/UNL  
Métodos Computacionais  
1<sup>st</sup> Semestre 2018/2019

## Dictionaries

- Arrays (vectors, matrices, or higher dimension) are very convenient structures to organize numerical information, since each “cell” should contain a number.
- In many cases, information is not only numeric, e.g. it includes text (we do not consider other types of information, such as visual or sound or video).
- In Python, such information can be grouped in lists, that may be composed of elements with different data types. However, the access to the elements of a list requires numerical indices, and this is somehow unnatural and inconvenient.
- Take for example the information about the employees of a certain company. For each employee we may consider:
  - **id** – integer, representing a unique identification number in the company
  - **name** – text, with the name of the employee
  - **date** – text, in format YYYY-MM-DD, representing the date of employment
  - **salary** – real number, representing the monthly salary of the employee

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3

## Dictionaries

- Although complex information is better maintained in a database, in simple applications, this heterogeneous information may be organized in a **dictionary**.
- Dictionaries are a special case of sets, in that they have elements that are not sorted by any index. Nevertheless, elements may be indexed, similarly to vectors, with some main differences.
  - Elements of a dictionary are key:value pairs; and
  - Unlike vectors (but like lists), values may be of different data types; and
  - Values are indexed keys that are strings (not numeric indices);
  - Values are accessed by specifying their keys, following the dictionary name, and a “.”.

### Example:

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3

- An employee, **emp**, may be represented by a dictionary, which is a set (curly brackets) whose elements have the form **key:value**)

`emp = {"id":98, name:"Rui Silva", "date":"2011-10-23", "salary":1654.3}`

# Dictionaries

- Several methods are defined for instances of the class dictionary that allow their manipulation.
- As sets, dictionaries may be created empty or by explicit specification of their elements.
- At any time, dictionaries may be cleared of all their elements

```
In : emp = {}  
In : emp  
Out: {}  
In : emp = {'id': 44, 'name': 'Rui Silva'}  
In : emp  
Out: {'id': 44, 'name': 'Rui Silva'}  
In : emp.clear()  
In : emp  
Out: {}
```

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3

## Dictionaries

- Once created the elements (items) of the dictionary may be accessed or changed by methods **get()** and **\_\_setitem\_\_()**.
- They can be called with the more usual **[ ]** notation.

```
In : emp = {'id': 67, 'name': 'Silva'}
In : emp
Out: {'id': 67, 'name': 'Silva'}
In : emp.get('id')
Out: 67
In : emp['name'] = "Rui Silva"
In : emp.__setitem__('id', 98)
In : emp['name']
Out: 'Rui Silva'
In : emp
Out: {'id': 98, 'name': 'Rui Silva'}
```

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3

## Dictionaries

- Items may be added to or deleted (and retrieved) from dictionaries with methods **update()** and **pop()**, respectively.
- Method **popitem()** deletes and retrieves, nondeterministically, some item of the dictionary

```
In : emp = {'id': 98, 'name': 'Rui Silva'}
In : emp.update({'date': '2011-10-23', 'salary': 1654.3})
In : emp
Out: {'id': 98, 'name': 'Rui Silva', 'date': '2011-10-23', 'salary': 1654.3}
In : emp.pop('salary')
Out: ('salary', 1654.3)
In : emp
Out: {'id': 98, 'name': 'Rui Silva', 'date': '2011-10-23'}
In : emp.pop('id')
Out: ('id', 98)
In : emp
Out: {'name': 'Rui Silva', 'date': '2011-10-23'}
```

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3

# Dictionaries

- The values and the keys of a dictionary can be obtained by methods **keys()**, **values()**, and **items()**.
- The information is returned in lists that can be subsequently iterated

```
In : emp
Out: {'id':98,'name':'Rui Silva','date':'2011-10-23'}
In : emp.keys()
Out: dict_keys(['id', 'name', 'date'])
In : emp.values()
Out: dict_values([98,'Rui Silva','2011-10-23'])
In : emp.items()
Out: dict_items([('id':98),('name':'Rui Silva'),('date':2011-10-23)])
In : for k in emp.keys():
...:     print(emp.get(k))
Out:
98
Rui Silva
2011-10-23
```

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3

## Dictionaries

- Finally, dictionaries may be copied, either in full, or only its structure with some of their keys.
- 

```
In : emp
Out: {'id':98,'name':'Rui Silva','date':'2011-10-23'}
In : x = emp.copy()
In : x
In : {'id':98,'name':'Rui Silva','date':'2011-10-23'}
In : ks = ('id', 'date')
In : y = emp.fromkeys()
In : y
Out: {'id':None, 'date':None}
```

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3



# Tables

- Many applications require to maintain several records in a “table”, i.e. a set of records of the same type, possibly indexed by a number or a “key”.

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3
56	Maria Santos	2008-12-18	1742.4
43	Carlos Dias	2003-04-12	2017.6
12	Isabel Rio	1987-09-05	2916.8

- Complex applications, requiring several tables, should of course be supported in databases. Nevertheless, for simple applications, tables can be directly modelled by more general programming languages.
- As discussed, heterogeneous records can be modelled in Python with dictionaries.
- Dictionaries may be grouped together in a table, typically as
  - lists (if they are to be indexed by numbers); or
  - dictionaries (if indexed by more general keys).

## Tables: Lists of Dictionaries

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3
56	Maria Santos	2008-12-18	1742.4
43	Carlos Dias	2003-04-12	2017.6
12	Isabel Rio	1987-09-05	2916.8

- When tables are organised as lists, the usual list operations and methods can be used to handle such tables, taking into account that elements are dictionaries.

```
In : emps = {}
In : emp ={'id':98,'name':'Rui Silva','date':'2011-10-23','salary':1654.3}
In : emps.append(emp)
In : emp ={'id':56,'name':'Maria Santos','date':'2008-12-18','salary':1742.4}
In : emps.append(emp)
In : emp ={'id':43,'name':Carlos dias,'date':'2003-04-12','salary':2017.6}
In : emps.append(emp)
In : emp ={'id':12,'name':Isabel Rio,'date':'1987-09-05','salary':2916.8}
In : emps.append(emp)
In : emps[2]['salary']. # 2 is the element position in the list
Out: 2017.6.3
```

## Tables: Dictionaries of Dictionaries

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3
56	Maria Santos	2008-12-18	1742.4
43	Carlos Dias	2003-04-12	2017.6
12	Isabel Rio	1987-09-05	2916.8

- When tables are organised as dictionaries of dictionaries, a key of the latter can be used as the key to the whole table (possibly duplicated in the records).

```
In : emps = []
In : emp ={'id':98,'name':'Rui Silva','date':'2011-10-23','salary':1654.3}
In : emps.update({98:emp})
In : emp ={'id':56,'name':'Maria Santos','date':'2008-12-18','salary':1742.4}
In : emps.update({56:emp})
In : emp ={'id':43,'name':Carlos Dias,'date':'2003-04-12','salary':2017.6}
In : emps.update({43:emp})
In : emp ={'id':12,'name':Isabel Rio,'date':'1987-09-05','salary':2916.8}
In : emps.update({12:emp})
In : emps[98]['salary'] # 98 is the id of the dictionary to be accessed
Out: 1654.3
```

## Lists of Dictionaries

- The following function projects a table (a dictionary of dictionaries) into some its columns, though iteration on their elements.

```
def emps_short(emps, keys):  
    """creates a dictionary of dictionaries, by  
    projecting the dictionaries into the given keys"""  
    shorts = {}  
    for key_1 in emps:  
        emp = emps[key_1]  
        short = {}  
        for key_2 in keys:  
            short.update({key_2:emp[key_2]})  
        shorts.update({key_1:short})  
    return shorts
```

id	name	date	salary (€)
98	Rui Silva	2011-10-23	1654.3
56	Maria Santos	2008-12-18	1742.4
43	Carlos Dias	2003-04-12	2017.6
12	Isabel Rio	1987-09-05	2916.8

```
In : ks = ('id', 'date')  
In : shorts = emps_short(emps,ks)  
In : shorts[43]  
Out: {'id':43,'name':Carlos Dias'}
```

## Handling Dictionaries from Files

- Typically, the information contained in a table is stored in a file, given the large volume of data it contains.
- Of course, processing this data directly from the file is very inefficient since
  - Access to files is sequential.
    - Once read say element  $i$ , reading element  $i-1$  requires reading the file again.
  - Access to files is slow:
    - Although disks nowadays are much faster than some years ago, namely the SSD disks that are fully electronic and have no mechanical components, its access is typically at least one order of magnitude slower than that to RAM memory, that have better channels to the CPU.
- Hence, processing data in a table, is done in up to 3 steps:
  1. Reading the table from a file to a structure array
  2. Process the data, e.g. changing elements of the table
  3. Write the new table into a file

## Reading Dictionaries from Files

- We illustrate the reading of a table from a file with a table created in CSV format (possibly from a spreadsheet as EXCEL) where
  - the first line indicates the name of the fields;
  - the the other lines contain the information of the records; and
  - fields are separated by commas (',')

**Table of Employees**

id	name	date	salary
98	Rui Silva	2011-10-23	1654.3
56	Maria Santos	2008-12-18	1742.4
43	Carlos Dias	2003-04-12	2017.6
12	Isabel Rio	1987-09-05	2916.8

```
Table of Employees  
id,name,date,salary  
98,Rui Silva,2011-10-23,1654.3  
56,Maria Santos,2008-12-18,1742.4  
43,Carlos Dias,2003-04-12,2017.6  
12,Isabel Rio,1987-09-05,2916.8
```

## Reading Tables of Dictionaries from Files

- Reading a file requires the following steps:
  1. Open the file in read mode
  2. Skip the first line
  3. Read the first line, stripping it from leading and trailing spaces - `strip()` method;
  4. Obtain the keys of the dictionaries by splitting the line: `split(',')` method;
  5. Read the following lines and close the file:
  6. Start the empty table;
  7. For each line read:
    1. Start an empty dictionary;
    2. Strip the line from leading and trailing spaces and split it with commas;
    3. For each key in the keys:
      1. Add the corresponding value to the dictionary
      2. Remove the first item from the line
    4. For each key in the keys
  8. Return the table
- The code is shown in the next slide

## Reading Tables of Dictionaries from Files

```
def read_emps(fname):
    """reads a table, as a list of dictionaries from a file
    with name fname. The keys are named in the first line, and
    the data items in the subsequent lines, all separated by commas"""
    fid = open(fname)
    fid.readline()
    keys_line = fid.readline().strip()
    keys = keys_line.split(',')
    lines = fid.readlines()
    fid.close()
    emps = []
    for line in lines:
        line = line.strip().split(',')
        emp = {}
        for key in keys:
            emp.update({key:line[0]})
            line = line[1:len(line)]
        emps.append(emp)
    return emps
```



## Writing Tables of Dictionaries into Files

- Writing a table to a file is done similarly.
  1. Open the file in write mode
  2. Write the title line
  3. For each key:
    1. Write the key and a trailing comma
  4. Replace the last comma by a new line
  5. Write the line
  6. For each emp in emps:
    1. Start an empty dictionary;
    2. Strip the line from leading and trailing spaces and split it with commas;
    3. For each key in the keys:
      1. Add the corresponding value and a comma to the line
    4. Replace the last comma by a new line
    5. Write the line
  7. Close the file
- The code is shown in the next slide

## Writing Tables of Dictionaries into Files

```
def write_emps(fname, emps):
    """reads a table, as a list of dictionaries from a file
    with name fname. The keys are named in the first line, and
    the data items in the subsequent lines, all separated
    by commas"""
    fid = open(fname, 'w')
    fid.write('Table of Employees\n')
    line = ""
    for key in emps[0].keys():
        line = line+key+", "
    line = line[0:len(line)-1]+"\\n"
    fid.write(line)
    for emp in emps:
        line = ""
        for key in emp.keys():
            line = line + emp[key] + ', '
        line = line[0:len(line)-1]+"\\n"
        fid.write(line)
    fid.close()
```

## Tables with Dictionaries – Processing

- Once the table is read into memory, we can process it, namely finding information contained in it.

### Three examples:

1. Find the average of the salaries of the employees;
  2. Find the oldest employee (according to the dates);
  3. Find the name of an employee with a given id
  4. Write a file with the employees earning more than a certain amount;
- In the first two cases, the structure array must be completely swept, whereas in the third case, the sweeping can stop once the employee is found.
  - In these cases, no information is written in a file.
  - In the last case a reduced table is written in a file
- These examples are left as exercises.